



MovemanSKG GOODS LIFT 146

The Goods Lift 146 is a purpose designed lift for transporting general goods. It is a totally self-contained unit complete with it's own enclosure which prevents the possibility of anybody or anything becoming trapped underneath the platform or falling off the platform. The enclosure is manufactured from reinforced heavy-duty steel panels to a powdercoat finish. All machinery is integrated within the unit and does not require any separate area. The landing doors are manually operated swing and can be latched in the open position when loading or unloading the lift. The doors are conventional single or double leaf swing type and are electrically and mechanically interlocked with the lift travel. The lift has a pit requirement of only 70-110mm dependent on capacity thus keeping building work to a minimum.



Specification details

- Capacity 500kg to 2000kg
- Goods Only
- Pit depth or ramp height only 70mm to 110mm (see table below)
- 'Self supporting' structure
- Speed 0.15m/sec
- Up to 9.0m travel available.
- Headroom just 2600mm at upper level
- Variable car platform sizes available (see table below)
- Single entry or open through entry options
- Hinged manual doors
- EC 'type tested' and conforms to Machinery Directive and EMC Directive
- Power supply – 415v 3ph 50Hz to a lockable isolator

Car Width		Car Depth		Car Height		Shaft Size	
From	To	From	To	From	To	Add to Width	Add to Depth
1000	2400	1060	2860	2000	2500	382mm	120mm

MovemanSKG
 (A Trading Division of Otis Ltd)
 123 Abbey Lane, Leicester LE4 5QX
 Tel: 0116 225 2100 Fax: 0116 261 0397
 Email: sales@movemanskgo.co.uk
 www.movemanskgo.co.uk

Registered Office:
 The Otis Building, 187 Twyford Abbey Road, London NW10 7DG Registered No. 147366